

Model	# of Cond	Cond gauge & Stranding	Shield Type & Coverage	Overall Diameter (inches)	Nominal Cap. (pF/ft @ 1 kHz)	Char. Imp @ 1Mhz	Available Colors	Weight per 1000 ft (lbs)
CONCERT1.*	1	20, 41 x 36	Braid, 90%	0.242	35	45	K, B, G, R, TI, W	40
DUAL-STUDIO1.*	2	18, 127 x 38	Braid, 95%	0.230 x 0.475	45	35	B, RB, TB	?
INST1.*	1	24, 19 x36	Spiral, 70%	0.242	25	60	K, B, G, P, R, W, Y, NB, NG, NO, NP, NY	35
INST1D	2	24, 19 x 36	Spiral, 70%	0.200 x 0.420	28	55	K	?
INST2.K	1	20, 26 x 34	Braid, 80%	0.195	45	35	K	27
INSTCLOTH.*	1	20, 41 x 36	Spiral, 95%	0.245	38	40	BKT, BKW, BLK, BLU, K, KBL, KEL, KNP, KR, KY, MBF, N, PUR, R, RWB, SCR, STL, TWD, VIN, Y	41
SOUNDFLEX.*	1	20, 41 x 36	Spiral, 95%	0.245	38	40	K, B, P, R	?
SOUNDHOSE.*	1	20, 41 x 36	Braid, 95%	0.245	38	40	B, G, K, M, N, O, P, R, Y	?
STUDIO1.*	1	18, 127 x 38	Braid, 95%	0.265	45	35	B, K, R, TB, TP, TR	41
ROADHOG.K	1	20, 41 x 36	Spiral, 95%	0.295	38	40	K	?
ROADHOG-CLOTH	1	20, 41 x 36	Spiral, 95%	0.310	38	40	K	?
GT-1.K	1	24, 7 x 32	Braid, 95%	0.275	21	75	K	?
GT-2.*	1	22, 19 x 34	Silver Braid, 95%	0.242	28	55	K, C, V(K cloth)	?
GT-3.K	1	18, 127 x 38	Braid, 95%	0.265	45	35	K	?
GT-4.K	1	20, 41 x 36	Braid, 95%	0.290	38	40	K	?
INST1AG	1	22, 19 x 34	Silver Braid, 95%	0.242	28	55	K	?